

**SURKON®****Endüstriyel El Pompaları - 350 Bar**

High Flow Handpump for Industrial Use



**Çift Etkili El Pompa**  
Double Acting Hand Pump

**Tek Etkili El Pompa**  
Single Acting Hand Pump



- » Çalışma basıncı 350 bar maks.
- » PMS tek ve PMI çift etkili model
- » Her modelde 3 farklı debi seçeneği
- » Yüksek debi,  $12 \text{ cm}^3$ ,  $25 \text{ cm}^3$  ve  $45 \text{ cm}^3$
- » Tek pistonlu çift yönlü yağ pompalama
- » Basma ve çekme her iki yönünde yağ basar
- » Emniyet valfi ile maksimum güvenlik sağlar
- » 10 litreye kadar 6 farklı yağ tankı seçeneği
- » Endüstriyel kullanıma uygun döküm yağ tankı
- » Manometre ve kaplin opsionel olarak sunulur
- » CE sertifikali, İtalyan malı, ISO-9001 Belgeli
- » Garanti hizmetleri Surkon tarafından sağlanır
- » Working pressure 350 bar max
- » PMS single, PMI double acting model
- » Three different flow rate of each model
- » Enable high flow  $12 \text{ cm}^3$ ,  $25 \text{ cm}^3$  and  $45 \text{ cm}^3$
- » Oil displacement in push and pull action
- » Equipped with over pressure safety valve
- » Cast oil tank options up to 10 liter capacity
- » Designed for heavy industrial use
- » Pressure gauge and coupling on option
- » Made in Italy by OMFB with CE marking

<b>Teknik Özellikler</b> <i>Technical Specifications</i>		<b>Birim</b> <i>Units</i>	<b>FLC12-SA</b>	<b>FLC25-SA</b>	<b>FLC45-SA</b>	<b>FLC12-DA</b>	<b>FLC25-DA</b>	<b>FLC45-DA</b>				
#	#	Tek Etki <i>Single Acting</i>	Tek Etki <i>Single Acting</i>	Tek Etki <i>Single Acting</i>	Çift Etki <i>Double Acting</i>	Çift Etki <i>Double Acting</i>	Çift Etki <i>Double Acting</i>					
Çalışma Basıncı <i>Working Pressure</i>	bar	350	300	270	350	300	270					
Kurs Boyundaki Toplam Debi <i>Oil Displacement per Stroke</i>	$\text{cm}^3$	12	25	45	12	25	45					
Basma-Çekme Debisi <i>Push / Pull Displacement</i>	$\text{cm}^3$	5.9 / 6.1	11.6 / 13.4	21.3 / 23.7	5.9 / 6.1	11.6 / 13.4	21.3 / 23.7					
Yağ Çıkış Bağlantısı <i>Oil Inlet Port</i>	NPT	1 x $3/8''$ NPT dışı			2 x $3/8''$ NPT dışı							
Uyumlu Yağ Tipi <i>Suitable Oil Type</i>	#	Shell Tellus 32 - Mobil DTE24										
Hızlı Birleştirme Kaplin Bağlantısı <i>Quick Coupling Connection</i>	NPT	Opsiyonel										
Manometre <i>Gauge</i>	G1/4"	Opsiyonel										
Tank Hariç Ağırlık <i>Weight Without Tank</i>	Kg	2.8	2.9	3.2	2.8	2.9	3.2					
Yağ Tankı Seçenekleri <i>Oil Tank Options</i>	#	1 - 2 - 3 - 5 - 7 - 10 litre										

